NSN 5365-00-776-2968

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-776-2968

Tien et mile at mape.//aeresaeegreap.cem/me//
Thread Pitch Diameters:
+4.2670 to 4.2720 inches
Thread Direction:
Right-hand
Casehardening Indicator:
Not casehardened
Width:
Between 0.365 inches and 0.385 inches
Overall Length:
Between 0.490 inches and 0.500 inches
Thread Size:
4.313-16
Bore Diameter:
Between 3.950 inches and 3.970 inches
Depth:
Between 0.060 inches and 0.080 inches
Bore Shape:
Straight
Screw Thread Series Designator:
Nonstandard
Drive Type:
Slotted face
Material Hardness Rating:
Between 32.0 rockwell c and 38.0 rockwell c
Accommodation Type And Quantity:
12 slots
Angle Between Accommodations In Deg:
30.0
Beveled Thread:
Not included
Bore Annular Internal Serration:
Not included
Setscrew Locking Notch:
Not included
Material:
Steel, ams 6322 or steel, ams 6323
Material:
Steel comp 8740 or steel comp 8740
Surface Treatment:
Tin flash, ams 2408
Surface Treatment:
Tin flash, ams 2408

NSN 5365-00-776-2968

Externally Threaded Ring - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d