

View Online at <https://aerobasegroup.com/nsn/5365-00-776-2968>

**Thread Pitch Diameters:**

+4.2670 to 4.2720 inches

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Width:**

Between 0.365 inches and 0.385 inches

**Overall Length:**

Between 0.490 inches and 0.500 inches

**Thread Size:**

4.313-16

**Bore Diameter:**

Between 3.950 inches and 3.970 inches

**Depth:**

Between 0.060 inches and 0.080 inches

**Bore Shape:**

Straight

**Screw Thread Series Designator:**

Nonstandard

**Drive Type:**

Slotted face

**Material Hardness Rating:**

Between 32.0 rockwell c and 38.0 rockwell c

**Accommodation Type And Quantity:**

12 slots

**Angle Between Accommodations In Deg:**

30.0

**Beveled Thread:**

Not included

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Not included

**Material:**

Steel, ams 6322 or steel, ams 6323

**Material:**

Steel comp 8740 or steel comp 8740

**Surface Treatment:**

Tin flash, ams 2408

**Surface Treatment:**

Tin flash, ams 2408

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T252-d