NSN 5365-00-781-9526

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-781-9526

Thread Pitch Diameters:
+5.3929 to 5.3969 inches
Thread Direction:
Right-hand
Casehardening Indicator:
Not casehardened
Width:
0.187 inches
Overall Length:
0.750 inches
Thread Size:
5.438-16
Bore Diameter:
3.562 inches
Depth:
0.250 inches
Bore Shape:
Straight
Screw Thread Series Designator:
Uns
Drive Type:
Slotted face
Material Hardness Rating:
Between 25.0 rockwell c and 30.0 rockwell c
Accommodation Type And Quantity:
6 slots
Angle Between Accommodations In Deg:
60.0
Beveled Thread:
Not included
Bore Annular Internal Serration:
Not included
Setscrew Locking Notch:
Not included
Material:
Steel, mil-s-6758
Material:
Steel comp 4130
Surface Treatment:
Cadmium
Surface Treatment:

Cadmium plated

NSN 5365-00-781-9526

Externally Threaded Ring - Page 2 of 2



Fsc Application Data	Fsc	Ap	plic	atio	n D	ata
----------------------	-----	----	------	------	-----	-----

Actuator, electromechanical linear

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d