NSN 5365-00-786-6665

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-786-6665 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Width: 0.156 inches **Overall Length:** 0.562 inches **Thread Size:** 4-7/8 in. -16 **Bore Diameter:** 4.380 inches Depth: 0.093 inches **Bore Shape:** Straight **Screw Thread Series Designator:** 16un **Drive Type:** Slotted face **Material Hardness Rating:** 33.0 rockwell c **Accommodation Type And Quantity:** 2 slots Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included Material: Steel, federal standard 66, aisi/sae 4130 Material: Steel comp 4130 **Surface Treatment:** Cadmium

Surface Treatment: Cadmium plated

NSN 5365-00-786-6665

Externally Threaded Ring - Page 2 of 2



Fsc Application Data	Fsc A	oplicatio	n Data:
----------------------	-------	-----------	---------

Guidance unit, guided missile

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d