## NSN 5365-00-796-2514

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-796-2514

Thread Pitch Diameters:
+10.1320 to 10.1420 inches
Thread Direction:
Right-hand
Casehardening Indicator:
Not casehardened
Chamfer Angle In Deg:
45.0
Chamfer Length:
0.031 inches
Width:
0.500 inches
Overall Length:
1.483 inches
Thread Size:
10.187 in. Diameter - 0.1p - 6 degrees - nr
Bore Diameter:
9.281 inches
Depth:
0.3125 inches
Bore Shape:
Straight
Screw Thread Series Designator:
Uns
Drive Type:
Externally slotted
Material Hardness Rating:
Between 30.0 rockwell c and 34.0 rockwell c
Thread Location:
End opposite drive end
Accommodation Type And Quantity:
6 slots
Angle Between Accommodations In Deg:
60.0
Beveled Thread:
Included
Bore Annular Internal Serration:
Not included
Setscrew Locking Notch:
Not included
Bore Edge Process:
<del>-</del>

## NSN 5365-00-796-2514

Fiig: T252-d

Externally Threaded Ring - Page 2 of 2



Process End Location:
End opposite drive end
Special Features:
10-15/16 in. Diameter by 0.436 in. Thkflange chamfered 1/8 in. By 45 degrees outside edge
Material:
Steel, sae 4135
Material:
Steel comp 4135
Fsc Application Data:
$Cradle\ assembly,\ cylinder\ assembly,\ concentric\ recoil,\ mount\ combination,\ gun,\ 76mm,\ m32$
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No