NSN 5365-00-802-2415

Thread Pitch Diameters: +5.8800 to 5.8900 inches

Thread Direction:

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-802-2415

Right-hand
Casehardening Indicator:
Not casehardened
Width:
Between 0.625 inches and 0.630 inches
Overall Length:
1.875 inches
Thread Size:
6.000-5
Bore Diameter:
5.000 inches
Depth:
0.500 inches
Bore Shape:
Straight
Screw Thread Series Designator:
Nonstandard
Drive Type:
Externally slotted
Material Hardness Rating:
Between 30.0 rockwell c and 35.0 rockwell c
Accommodation Type And Quantity:
18 slots
Angle Between Accommodations In Deg:
20.0
Beveled Thread:
Not included
Bore Annular Internal Serration:
Not included
Setscrew Locking Notch:
Not included
Special Features:
One external groove 0.250in.W.0.250 in.Deep, located0.375 in.From drive end
Material:
Steel, federal standard 66, aisi/sae 4140 or steel, federal standard 66, aisi/sae 8645
Material:
Steel comp 4140 or steel comp 8645
Surface Treatment:
Phosphate

NSN 5365-00-802-2415

Externally Threaded Ring - Page 2 of 2



Surface Treatment:
Phosphate

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d