NSN 5365-00-809-1926

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-809-1926 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Chamfer Angle In Deg: 45.0 **Chamfer Length:** 0.050 inches Width: 0.090 inches **Overall Length:** 0.500 inches **Thread Size:** 0.750-20 **Bore Diameter:** 0.560 inches Depth: 0.090 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Unef **Drive Type:** Slotted face **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Bore Edge Process:** Chamfered **Process End Location:** Both ends **Special Features:**

Has a 0.062 in. W by 0.310 in. L by 0.040 in. D notch in threads located randomly but notch end must be 0.090 in. From bottom edge

NSN 5365-00-809-1926

Externally Threaded Ring - Page 2 of 2



ΝЛ	2+	er	in	١.
IVI	aı	ŒI.	a	ı .

Steel, corrosion resisting, comp 303

Material:

Steel, corrosion resisting, comp 303

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d