

View Online at <https://aerobasegroup.com/nsn/5365-00-813-2624>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Chamfer Angle In Deg:**

45.0

**Chamfer Length:**

0.020 inches

**Width:**

0.063 inches

**Overall Length:**

0.380 inches

**Thread Size:**

5/8 in. -24

**Bore Diameter:**

0.421 inches

**Depth:**

0.063 inches

**Bore Shape:**

Straight

**Screw Thread Series Designator:**

Unef

**Drive Type:**

Slotted face

**Accommodation Type And Quantity:**

2 slots

**Angle Between Accommodations In Deg:**

180.0

**Beveled Thread:**

Not included

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Not included

**Bore Edge Process:**

Chamfered

**Process End Location:**

Drive end

**Material:**

Steel, sae 1113

**Material:**

Steel comp 1213

**Surface Treatment:**

Cadmium

**Surface Treatment:**

Cadmium plated

**Fsc Application Data:**

Valve, hydraulic, aircraft

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T252-d