

View Online at <https://aerobasegroup.com/nsn/5365-00-820-3158>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Overall Length:**

Between 0.320 inches and 0.330 inches

**Diameter:**

Between 0.188 inches and 0.198 inches

**Thread Size:**

2-9/16 in.-18

**Bore Diameter:**

Between 1.500 inches and 1.510 inches

**Depth:**

0.205 inches

**Bore Shape:**

Straight

**Screw Thread Series Designator:**

Ns

**Drive Type:**

Drilled face

**Accommodation Type And Quantity:**

4 holes

**Angle Between Accommodations In Deg:**

90.0

**Radius From Geometric Axis To Accommodation:**

0.937 inches

**Beveled Thread:**

Not included

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Not included

**Special Features:**

Noneface of ring countersunk both sides 1/16 in. Deep and 2-1/4 in. Dia

**Material:**

Steel, aisi mt1015

**Material:**

Steel comp mt1015

**Surface Treatment:**

Cadmium

**Surface Treatment:**

Cadmium plated

**Fsc Application Data:**

No-back shaft bearing, traverse mechanism, howitzer, self-propelled

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T252-d