

View Online at <https://aerobasegroup.com/nsn/5365-00-824-6009>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Chamfer Angle In Deg:**

45.0

**Chamfer Length:**

0.030 inches

**Width:**

0.190 inches

**Overall Length:**

0.375 inches

**Thread Size:**

2-3/4 in. -16n

**Bore Diameter:**

1.905 inches

**Depth:**

0.120 inches

**Bore Shape:**

Straight

**Screw Thread Series Designator:**

Unf

**Drive Type:**

Slotted face

**Thread Location:**

Both ends

**Accommodation Type And Quantity:**

4 slots

**Angle Between Accommodations In Deg:**

90.0

**Beveled Thread:**

Included

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Included

**Bore Edge Process:**

Chamfered

**Process End Location:**

Both ends

**Material:**

Aluminum alloy, qq-a-225/4, t6

**Material:**

Aluminum alloy 2014

**Surface Treatment:**

Anodize

**Surface Treatment:**

Anodized

**Fsc Application Data:**

Drag strut, aircraft landing gear

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T252-d