## NSN 5365-00-824-6009

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-824-6009 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 45.0 **Chamfer Length:** 0.030 inches Width: 0.190 inches **Overall Length:** 0.375 inches **Thread Size:** 2-3/4 in. -16n **Bore Diameter:** 1.905 inches Depth: 0.120 inches Bore Shape: Straight **Screw Thread Series Designator:** Unf **Drive Type:** Slotted face **Thread Location:** 

Both ends **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: 90.0 **Beveled Thread:** Included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Included **Bore Edge Process:** Chamfered **Process End Location:** Both ends

## **NSN 5365-00-824-6009**Externally Threaded Ring - Page 2 of 2



Material:
Aluminum alloy, qq-a-225/4, to
Material:
Aluminum alloy 2014
Surface Treatment:
Anodize
Surface Treatment:
Anodized
Fsc Application Data:
Drag strut, aircraft landing gear
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: T252-d