## NSN 5365-00-825-7844

Sleeve Spacer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5365-00-825-7844

Overall Length: Between 0.8390 inches and 0.8490 inches  Body Outside Diameter: Between 0.3020 inches and 0.3220 inches  Body Inside Diameter: Between 0.1940 inches and 0.2340 inches  Corner Shape: Square all corners  Special Features: Gray anodize or blue chromate  Material: Aluminum alloy 2024  Material Specification:  Ww-t-700/3, t3, type 1 federal specification single material response or qq-a-225/6, t4 federal specification single material response  Surface Treatment: Anodize or chromate  Surface Treatment Specification: Mil-a-8625, type 1 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response  Style Designator: 17c solid, plain, no outside flanges  Specification Data:  80205-nas43 professional/industrial association standard
Between 0.3020 inches and 0.3220 inches  Body Inside Diameter:  Between 0.1940 inches and 0.2340 inches  Corner Shape:  Square all corners  Special Features:  Gray anodize or blue chromate  Material:  Aluminum alloy 2024  Material Specification:  Ww-t-700/3, t3, type 1 federal specification single material response or qq-a-225/6, t4 federal specification single material response  Surface Treatment:  Anodize or chromate  Surface Treatment Specification:  Mil-a-8625, type 1 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response  Style Designator:  17c solid, plain, no outside flanges  Specification Data:
Between 0.3020 inches and 0.3220 inches  Body Inside Diameter:  Between 0.1940 inches and 0.2340 inches  Corner Shape:  Square all corners  Special Features:  Gray anodize or blue chromate  Material:  Aluminum alloy 2024  Material Specification:  Ww-t-700/3, t3, type 1 federal specification single material response or qq-a-225/6, t4 federal specification single material response  Surface Treatment:  Anodize or chromate  Surface Treatment Specification:  Mil-a-8625, type 1 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response  Style Designator:  17c solid, plain, no outside flanges  Specification Data:
Between 0.1940 inches and 0.2340 inches  Corner Shape: Square all corners  Special Features: Gray anodize or blue chromate  Material: Aluminum alloy 2024  Material Specification:  Ww-t-700/3, 13, type 1 federal specification single material response or qq-a-225/6, t4 federal specification single material response  Surface Treatment: Anodize or chromate  Surface Treatment Specification: Mil-a-8625, type 1 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response  Style Designator: 17c solid, plain, no outside flanges  Specification Data:
Between 0.1940 inches and 0.2340 inches  Corner Shape:  Square all corners  Special Features:  Gray anodize or blue chromate  Material:  Aluminum alloy 2024  Material Specification:  Ww-t-700/3, t3, type 1 federal specification single material response or qq-a-225/6, t4 federal specification single material response  Surface Treatment:  Anodize or chromate  Surface Treatment Specification:  Mil-a-8625, type 1 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response  Style Designator:  17c solid, plain, no outside flanges  Specification Data:
Corner Shape: Square all corners Special Features: Gray anodize or blue chromate Material: Aluminum alloy 2024 Material Specification: Ww-t-700/3, t3, type 1 federal specification single material response or qq-a-225/6, t4 federal specification single material response Surface Treatment: Anodize or chromate Surface Treatment Specification: Mil-a-8625, type 1 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response Style Designator: 17c solid, plain, no outside flanges Specification Data:
Square all corners  Special Features: Gray anodize or blue chromate  Material: Aluminum alloy 2024  Material Specification:  Ww-t-700/3, t3, type 1 federal specification single material response or qq-a-225/6, t4 federal specification single material response  Surface Treatment: Anodize or chromate  Surface Treatment Specification: Mil-a-8625, type 1 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response  Style Designator:  17c solid, plain, no outside flanges  Specification Data:
Special Features: Gray anodize or blue chromate  Material: Aluminum alloy 2024  Material Specification:  Ww-t-700/3, 13, type 1 federal specification single material response or qq-a-225/6, t4 federal specification single material response  Surface Treatment: Anodize or chromate  Surface Treatment Specification:  Mil-a-8625, type 1 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response  Style Designator:  17c solid, plain, no outside flanges  Specification Data:
Gray anodize or blue chromate  Material: Aluminum alloy 2024  Material Specification:  Ww-t-700/3, t3, type 1 federal specification single material response or qq-a-225/6, t4 federal specification single material response  Surface Treatment:  Anodize or chromate  Surface Treatment Specification:  Mil-a-8625, type 1 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response  Style Designator:  17c solid, plain, no outside flanges  Specification Data:
Material: Aluminum alloy 2024  Material Specification:  Ww-t-700/3, t3, type 1 federal specification single material response or qq-a-225/6, t4 federal specification single material response Surface Treatment:  Anodize or chromate  Surface Treatment Specification:  Mil-a-8625, type 1 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response Style Designator:  17c solid, plain, no outside flanges  Specification Data:
Material Specification:  Ww-t-700/3, t3, type 1 federal specification single material response or qq-a-225/6, t4 federal specification single material response Surface Treatment:  Anodize or chromate  Surface Treatment Specification:  Mil-a-8625, type 1 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response  Style Designator:  17c solid, plain, no outside flanges  Specification Data:
Material Specification:  Ww-t-700/3, t3, type 1 federal specification single material response or qq-a-225/6, t4 federal specification single material response Surface Treatment:  Anodize or chromate  Surface Treatment Specification:  Mil-a-8625, type 1 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response Style Designator:  17c solid, plain, no outside flanges  Specification Data:
Ww-t-700/3, t3, type 1 federal specification single material response or qq-a-225/6, t4 federal specification single material response Surface Treatment:  Anodize or chromate  Surface Treatment Specification:  Mil-a-8625, type 1 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response  Style Designator:  17c solid, plain, no outside flanges  Specification Data:
Surface Treatment: Anodize or chromate Surface Treatment Specification: Mil-a-8625, type 1 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response Style Designator: 17c solid, plain, no outside flanges Specification Data:
Anodize or chromate  Surface Treatment Specification:  Mil-a-8625, type 1 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response  Style Designator:  17c solid, plain, no outside flanges  Specification Data:
Surface Treatment Specification:  Mil-a-8625, type 1 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response  Style Designator:  17c solid, plain, no outside flanges  Specification Data:
Mil-a-8625, type 1 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response  Style Designator:  17c solid, plain, no outside flanges  Specification Data:
Style Designator:  17c solid, plain, no outside flanges  Specification Data:
17c solid, plain, no outside flanges  Specification Data:
Specification Data:
80205-pas/3 professional/industrial association standard
ของ จากลอง จากเลอง เกิดเกิดเกิดเกิดเกิดเกิดเกิดเกิดเกิดเกิด
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A045a0
Mil-std (military Standard):
Mil-a-8625 spec.