Mount, combination gun, m78, 90-mm

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-838-4758

| Thread Class:                               |  |  |
|---|--|--|
| 2a  |  |  |
| Thread Direction:                           |  |  |
| Right-hand                                  |  |  |
| Casehardening Indicator:                    |  |  |
| Not casehardened                            |  |  |
| Width:                                      |  |  |
| 0.094 inches                                |  |  |
| Overall Length:                             |  |  |
| 0.250 inches                                |  |  |
| Thread Size:                                |  |  |
| 1 in14                                      |  |  |
| Bore Diameter:                              |  |  |
| 0.406 inches                                |  |  |
| Depth:                                      |  |  |
| 0.094 inches                                |  |  |
| Bore Shape:                                 |  |  |
| Straight                                    |  |  |
| Screw Thread Series Designator:             |  |  |
| Unf   |  |  |
| Drive Type:                                 |  |  |
| Slotted face                                |  |  |
| Accommodation Type And Quantity:            |  |  |
| 2 slots                                     |  |  |
| Angle Between Accommodations In Deg:        |  |  |
| 180.0                                       |  |  |
| Beveled Thread:                             |  |  |
| Not included                                |  |  |
| Bore Annular Internal Serration:            |  |  |
| Not included                                |  |  |
| Setscrew Locking Notch:                     |  |  |
| Not included                                |  |  |
| Material:                                   |  |  |
| Steel, qq-s-633 amend 2, fs 1018 to fs 1025 |  |  |
| Material:                                   |  |  |
| Steel, qq-s-633 amend 2, fs 1018 to fs 1025 |  |  |
| Surface Treatment:                          |  |  |
| Phosphate                                   |  |  |
| Surface Treatment:                          |  |  |
| Phosphate                                   |  |  |
| Fsc Application Data:                       |  |  |
| Mount combination auto m70,00 mm            |  |  |

## NSN 5365-00-838-4758

Externally Threaded Ring - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d

