NSN 5365-00-840-1785

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-840-1785 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 45.0 **Chamfer Length:** 0.060 inches Width: 0.190 inches **Overall Length:** 1.010 inches **Thread Size:** 1.437-16 **Bore Diameter:** 0.940 inches Depth: 0.250 inches Bore Shape: Straight **Screw Thread Series Designator:** Un **Drive Type:** Slotted face **Material Hardness Rating:** 33.000 rockwell c **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: 60.0 **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Included **Bore Edge Process:** Chamfered **Process End Location:**

Both ends

NSN 5365-00-840-1785

Externally Threaded Ring - Page 2 of 2



N/I	9	te	rı	2	

Steel, qq-s-634, comp 1040-canceled or steel, sae 1052 or steel, qq-s-637, comp 1141

Material:

Steel comp 1040 or steel comp 1552 or steel comp 1141

Fsc Application Data:

20 mm repositioner, machine gun

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T252-d