## NSN 5365-00-851-7323

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-851-7323

Thread Pitch Diameters:
+0.9496/+0.9535 inches
Thread Direction:
Right-hand
Casehardening Indicator:
Not casehardened
Width:
0.120 inches
Overall Length:
0.550 inches
End Radius:
0.060 inches
Thread Size:
1.000 in14
Bore Diameter:
Between 0.561 inches and 0.570 inches
Depth:
0.120 inches
Bore Shape:
Straight
Screw Thread Series Designator:
Uns
Uns Drive Type:
Drive Type:
Drive Type: Slotted face
Drive Type: Slotted face Accommodation Type And Quantity:
Drive Type: Slotted face Accommodation Type And Quantity: 4 slots
Drive Type: Slotted face Accommodation Type And Quantity: 4 slots Angle Between Accommodations In Deg:
Drive Type: Slotted face Accommodation Type And Quantity: 4 slots Angle Between Accommodations In Deg: 90.0
Drive Type: Slotted face Accommodation Type And Quantity: 4 slots Angle Between Accommodations In Deg: 90.0 Beveled Thread:
Drive Type: Slotted face Accommodation Type And Quantity: 4 slots Angle Between Accommodations In Deg: 90.0 Beveled Thread: Not included
Drive Type: Slotted face Accommodation Type And Quantity: 4 slots Angle Between Accommodations In Deg: 90.0 Beveled Thread: Not included Bore Annular Internal Serration:
Drive Type: Slotted face Accommodation Type And Quantity: 4 slots Angle Between Accommodations In Deg: 90.0 Beveled Thread: Not included Bore Annular Internal Serration: Not included
Drive Type: Slotted face Accommodation Type And Quantity: 4 slots Angle Between Accommodations In Deg: 90.0 Beveled Thread: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch:
Drive Type: Slotted face Accommodation Type And Quantity: 4 slots Angle Between Accommodations In Deg: 90.0 Beveled Thread: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included
Drive Type: Slotted face Accommodation Type And Quantity: 4 slots Angle Between Accommodations In Deg: 90.0 Beveled Thread: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Bore Edge Process:
Drive Type: Slotted face Accommodation Type And Quantity: 4 slots Angle Between Accommodations In Deg: 90.0 Beveled Thread: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Bore Edge Process: Rounded
Drive Type: Slotted face Accommodation Type And Quantity: 4 slots Angle Between Accommodations In Deg: 90.0 Beveled Thread: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Bore Edge Process: Rounded Process End Location:
Drive Type: Slotted face Accommodation Type And Quantity: 4 slots Angle Between Accommodations In Deg: 90.0 Beveled Thread: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Bore Edge Process: Rounded Process End Location: End opposite drive end
Drive Type: Slotted face Accommodation Type And Quantity: 4 slots Angle Between Accommodations In Deg: 90.0 Beveled Thread: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Bore Edge Process: Rounded Process End Location: End opposite drive end Material:

## NSN 5365-00-851-7323

Externally Threaded Ring - Page 2 of 2



Surface Treatmer
------------------

Anodize

**Surface Treatment:** 

Anodized

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T252-d