

View Online at <https://aerobasegroup.com/nsn/5365-00-856-7295>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Chamfer Angle In Deg:**

45.0

**Chamfer Length:**

0.030 inches

**Overall Length:**

0.560 inches

**Diameter:**

0.188 inches

**Thread Size:**

2 in.-16

**Bore Diameter:**

1.093 inches

**Depth:**

0.370 inches

**Bore Shape:**

Straight

**Screw Thread Series Designator:**

Unef

**Drive Type:**

Drilled face

**Material Hardness Rating:**

Not rated

**Thread Location:**

Both ends

**Accommodation Type And Quantity:**

4 holes

**Angle Between Accommodations In Deg:**

90.0

**Radius From Geometric Axis To Accommodation:**

0.756 inches

**Beveled Thread:**

Included

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Not included

**Bore Edge Process:**

Chamfered

**Process End Location:**

End opposite drive end

**Material:**

Aluminum alloy, qq-a-268, t4-canceled

**Material:**

Aluminum alloy 2024

**Surface Treatment:**

Anodize

**Surface Treatment:**

Anodized

**Fsc Application Data:**

Drive mechanism, helicopter

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T252-d