Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-880-0853

| Thread Class: | | | |
|---------------------|----------------------|--|--|
| 2a | | | |
| Thread Direction: | | | |
| Right-hand | | | |
| Casehardening Ind | icator: | | |
| Not casehardened | | | |
| Width: | | | |
| 0.080 inches | | | |
| Overall Length: | | | |
| 0.218 inches | | | |
| Thread Size: | | | |
| 9/16 in40 | | | |
| Bore Diameter: | | | |
| 0.400 inches | | | |
| Depth: | | | |
| 0.045 inches | | | |
| Bore Shape: | | | |
| Straight | | | |
| Screw Thread Serie | es Designator: | | |
| Uns | | | |
| Drive Type: | | | |
| Slotted face | | | |
| Accommodation T | /pe And Quantity: | | |
| 2 slots | | | |
| Angle Between Ac | commodations In Deg: | | |
| 180.0 | | | |
| Beveled Thread: | | | |
| Not included | | | |
| Bore Annular Inter | nal Serration: | | |
| Not included | | | |
| Setscrew Locking | Notch: | | |
| Not included | | | |
| Material: | | | |
| Steel | | | |
| Material: | | | |
| Steel | | | |
| Surface Treatment | : | | |
| Oxide | | | |
| Surface Treatment | : | | |
| Black oxide | | | |
| Fsc Application Da | ta: | | |
| Gyroscope, displace | | | |
| | | | |

NSN 5365-00-880-0853

Externally Threaded Ring - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d

