

View Online at <https://aerobasegroup.com/nsn/5365-00-882-2318>

Thread Class:

3a

Thread Pitch Diameters:

+5.6004/+5.6024 inches

Thread Direction:

Right-hand

Casehardening Indicator:

Not casehardened

Chamfer Angle In Deg:

45.0

Chamfer Length:

0.0625 inches

Overall Length:

0.687 inches

Diameter:

0.281 inches

Thread Size:

5-21/32 in.-12 (push)

Bore Diameter:

3.750 inches

Depth:

0.687 inches

Bore Shape:

Straight

Screw Thread Series Designator:

N butt

Drive Type:

Drilled face

Material Hardness Rating:

C30 to c36

Accommodation Type And Quantity:

4 holes

Angle Between Accommodations In Deg:

90.0

Radius From Geometric Axis To Accommodation:

2.250 inches

Beveled Thread:

Not included

Bore Annular Internal Serration:

Not included

Setscrew Locking Notch:

Not included

Bore Edge Process:

Chamfered

Process End Location:

Both ends

Material:

Steel, qq-s-624, comp 4140-canceled or steel, qq-s-624, comp 5140-canceled or steel, qq-s-624, comp 8640-canceled or steel, qq-s-624, comp 8740-canceled

Material:

Steel comp 4140 or steel comp 5140 or steel comp 8640 or steel comp 8740

Surface Treatment:

Phosphate

Surface Treatment:

Phosphate

Fsc Application Data:

Shock absorber, lockout vehicular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T252-d