NSN 5365-00-890-3902

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-890-3902

Thread Class:
2a
Thread Direction:
Right-hand
Casehardening Indicator:
Not casehardened
Overall Length:
0.156 inches
Diameter:
0.038 inches
Thread Size:
0.312-64
Bore Diameter:
Between 0.156 inches and 0.161 inches
Depth:
0.047 inches
Bore Shape:
Straight
Screw Thread Series Designator:
Uns
Drive Type:
Drilled face
Accommodation Type And Quantity:
8 holes
Angle Between Accommodations In Deg:
45.0
Radius From Geometric Axis To Accommodation:
0.111 inches
Beveled Thread:
Not included
Bore Annular Internal Serration:
Not included
Setscrew Locking Notch:
Not included
Special Features:
Counterbore end opposite drive end 0.234 in. Dia, 0.062 in. Min 0.067 in. Maximum depth
Material:
Steel, qq-s-764 class 416 condition a
Material:
Steel, qq-s-764 class 416 condition a
Surface Treatment:
Passivate

NSN 5365-00-890-3902

Externally Threaded Ring - Page 2 of 2



_	•		_				
<u>ن</u>	urfa	\sim	l r	2	ŀm	Δn	

Passivated

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d