

View Online at <https://aerobasegroup.com/nsn/5365-00-891-1437>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Chamfer Angle In Deg:**

45.0

**Chamfer Length:**

0.070 inches

**Width:**

0.380 inches

**Overall Length:**

1.560 inches

**Thread Size:**

5-5/8 in. -12

**Bore Diameter:**

Between 4.757 inches and 4.767 inches

**Depth:**

0.380 inches

**Bore Shape:**

Straight

**Screw Thread Series Designator:**

Uns

**Drive Type:**

Slotted face

**Thread Location:**

End opposite drive end

**Accommodation Type And Quantity:**

4 slots

**Angle Between Accommodations In Deg:**

90.0

**Beveled Thread:**

Included

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Not included

**Bore Edge Process:**

Chamfered

**Process End Location:**

Both ends

**Special Features:**

Bore opposite to drive end counterbored, 4.954 in. To 4.957 in. Dia, 1.066 in. To 1.074 in. Deep, 4 drilled holes equally spaced, 0.070 in. Dia

**Material:**

Aluminum alloy, qq-a-225/9, t6

**Material:**

Aluminum alloy 7075

**Surface Treatment:**

Anodized

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T252-d