NSN 5365-00-893-5244



Externally Threaded Ring - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5365-00-893-5244 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Overall Length:** 0.150 inches Diameter: 0.070 inches **Thread Size:** 1.6250-32 **Bore Diameter:** 0.950 inches Depth: 0.070 inches **End Application:** M110 howitzer family Bore Shape: Straight **Screw Thread Series Designator:** Uns **Drive Type:** Drilled face **Accommodation Type And Quantity:** 2 holes Angle Between Accommodations In Deg: **Radius From Geometric Axis To Accommodation:** 0.6875 inches **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Special Features:** Counterbore 0.468 deep x 1.250 diameter and peripheral relief 0.005 deep x 0.0775 w on face opposite drive holes; enamel od on drive face Material:

Material:

Aluminum alloy 6061

Aluminum alloy, ww-t-700/6, alloy 6061, t4

NSN 5365-00-893-5244

Externally Threaded Ring - Page 2 of 2



_	•	_			
•	ırt 🔿 🖊	ו סי	reat	ma	nt.
Ju	II I av	,	ıcaı		IIL.

Enamel

Surface Treatment:

Enamel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d