NSN 5365-00-895-9410

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-895-9410 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 50.0 **Chamfer Length:** 0.040 inches Width: 0.500 inches **Overall Length:** Between 0.430 inches and 0.450 inches **Thread Size:** 9.3875-12 **Bore Diameter:** Between 8.670 inches and 8.690 inches Depth: Between 0.160 inches and 0.180 inches Bore Shape: Straight **Screw Thread Series Designator:** Uns **Drive Type:** Slotted inner face **Accommodation Type And Quantity:** 4 slots Angle Between Accommodations In Deg: 90.0 **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Bore Edge Process:** Chamfered **Process End Location:** End opposite drive end **Special Features:** Max surface finish, all surfaces 125 microinches aa

NSN 5365-00-895-9410

Externally Threaded Ring - Page 2 of 2



| ate | |
|-----|--|
| | |
| | |

Steel, ams 6415 comp 9340

Material:

Steel, ams 6415 comp 9340

Surface Treatment:

Black oxide coated mil-c-13924 class 1 grade a

Surface Treatment:

Black oxide coated mil-c-13924 class 1 grade a

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d