NSN 5365-00-899-6938

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-899-6938 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 5.0 **Chamfer Length:** 0.0312 inches **Overall Length:** 0.240 inches Diameter: 0.0938 inches **Thread Size:** 0.750-32 **Bore Diameter:** 0.250 inches Depth: 0.0938 inches **End Application:** M110 howitzer family **Bore Shape:** Straight **Screw Thread Series Designator:** Ns **Drive Type:** Drilled face **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: **Radius From Geometric Axis To Accommodation:** 0.250 inches **Beveled Thread:** Not included **Bore Annular Internal Serration: Setscrew Locking Notch:**

Not included

Setscrew Locking Not
Not included

Bore Edge Process:
Chamfered

NSN 5365-00-899-6938Externally Threaded Ring - Page 2 of 2



Process End Location:
End opposite drive end
Special Features:
Enamel forest green on drive holeface
Material:
Steel, qq-s-763, class 303, cond a
Material:
Steel comp 303
Surface Treatment:
Passivate and enamel
Surface Treatment:
Passivated and enamel
Fsc Application Data:
Mount, telescope, integrated with fire control equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T252-d