NSN 5365-00-900-1027



Externally Threaded Ring - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5365-00-900-1027 **Thread Pitch Diameters:** +0.6270/+0.6297 inches **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Chamfer Angle In Deg: 45.0 **Chamfer Length:** Between 0.020 inches and 0.025 inches Width: 0.062 inches **Overall Length:** 0.159 inches **Thread Size:** 0.650-32 **Bore Diameter:** Between 0.644 inches and 0.650 inches Depth: 0.050 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Unef **Drive Type:** Slotted face **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Bore Edge Process:** Chamfered

Process End Location: End opposite drive end

Material:

Steel, qq-s-763, class 416, cond h

NSN 5365-00-900-1027

Externally Threaded Ring - Page 2 of 2



М	ate	ria	١.
IVI	ale	па	ı .

Steel comp 416

Surface Treatment:

Passivate

Surface Treatment:

Passivated

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d