

View Online at <https://aerobasegroup.com/nsn/5365-00-903-6668>

**Thread Pitch Diameters:**

+2.5174/+2.5219 inches

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Overall Length:**

Between 0.540 inches and 0.560 inches

**Diameter:**

Between 0.270 inches and 0.290 inches

**Thread Size:**

2.562-16

**Bore Diameter:**

Between 1.500 inches and 1.520 inches

**Depth:**

Between 0.540 inches and 0.560 inches

**Bore Shape:**

Straight

**Screw Thread Series Designator:**

Uns

**Drive Type:**

Drilled face

**Accommodation Type And Quantity:**

2 holes

**Angle Between Accommodations In Deg:**

180.0

**Radius From Geometric Axis To Accommodation:**

1.000 inches

**Beveled Thread:**

Not included

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Not included

**Material:**

Steel, fed stdno. 668, aisi c1 015 to 1025

**Material:**

Steel, fed stdno. 668, aisi c1 015 to 1025

**Surface Treatment:**

Cadmium

**Surface Treatment:**

Cadmium plated

**Fsc Application Data:**

Clutch angle drive, combat vehicle, full-tracked

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T252-d