## NSN 5365-00-906-1824

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-906-1824 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 45.0 **Chamfer Length:** 0.040 inches **Overall Length:** 0.219 inches Diameter: Between 0.155 inches and 0.159 inches **Thread Size:** 2.125-16 **Bore Diameter:** Between 1.526 inches and 1.536 inches Depth: 0.125 inches Bore Shape: Straight **Screw Thread Series Designator:** Un **Drive Type:** Drilled face **Thread Location:** Both ends **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: **Radius From Geometric Axis To Accommodation:** 0.912 inches **Beveled Thread:** Included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** 

Not included

**Bore Edge Process:** 

Chamfered

## NSN 5365-00-906-1824

Externally Threaded Ring - Page 2 of 2



## **Process End Location:** End opposite drive end **Special Features:** Drive end counterbored 1.645 in. Diameter 0.078 in. Deep Material: Steel, astm a276 type 303 or steel, astm a276 type 416 cond a Material: Steel, astm a276 type 303 or steel, astm a276 type 416 cond a **Surface Treatment:** Passivate **Surface Treatment:** Passivated Shelf Life: N/a **Unit Of Measure:** Demilitarization:

No **Fiig:** T252-d