

View Online at <https://aerobasegroup.com/nsn/5365-00-907-6786>

Thread Pitch Diameters:

+5.807/+5.944 inches

Thread Direction:

Right-hand

Casehardening Indicator:

Not casehardened

Width:

0.400 inches

Overall Length:

1.380 inches

Thread Size:

5.9449d-0.2362 p-mod 6deg-r

Bore Diameter:

5.118 inches

Depth:

0.200 inches

End Application:

M158 gun mount

Bore Shape:

Straight

Screw Thread Series Designator:

Special

Drive Type:

Slotted face

Material Hardness Rating:

Between 16.0 rockwell c and 27.0 rockwell c

Thread Location:

Drive end

Accommodation Type And Quantity:

4 slots

Angle Between Accommodations In Deg:

90.0

Beveled Thread:

Not included

Bore Annular Internal Serration:

Included

Setscrew Locking Notch:

Not included

Special Features:

5.2756d-0.1575 p-mod 6 deg-r female thread 0.490 deep on drive end; ring groove 5.300 diameter x 0.160 w 0.630 from drive end

Material:

Steel, astm a108 or steel, astm a322, grade 4140

Material:

Steel comp 1008 or steel comp 1010 or steel comp 1015 or steel comp 1016 or steel comp 1018 or steel comp 1020 or steel comp 1022 or steel comp 1025 or steel comp 1030 or steel comp 1035 or steel comp 1040 or steel comp 1045 or steel comp 1050 or steel comp 1095 or steel comp 1115 or steel comp 1117 or steel comp 1118 or steel comp 1137 or steel comp 1141 or steel comp 1144 or steel comp 1151 or steel comp 1214 or steel comp 1211 or steel comp 1212 or steel comp 1213 or steel comp 1215 or steel comp 4140

Surface Treatment:

Oxide

Surface Treatment:

Black oxide, mil-c-13924, class 1

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T252-d