## NSN 5365-00-910-5248

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-910-5248

Thread Pitch Diameters:
+6.1282/+6.1334 inches
Thread Direction:
Right-hand
Casehardening Indicator:
Not casehardened
Width:
0.440 inches
Overall Length:
1.620 inches
Diameter:
0.440 inches
Thread Size:
6-3/16 in12
Bore Diameter:
5.527 inches
Bore Shape:
Straight
Screw Thread Series Designator:
Uns
Drive Type:
Lug face
Thread Location:
Both ends
Accommodation Type And Quantity:
4 lugs
Angle Between Accommodations In Deg:
90.0
Radius From Geometric Axis To Accommodation:
5.971 inches
Beveled Thread:
Included
Bore Annular Internal Serration:
Not included
Setscrew Locking Notch:
Not included
Special Features:
Center hole is counterbored opposited drive end to 5.752 in. Min, 5.756 in. Maximum diameter and 1.300 in. Deep
Height:
0.250 inches
Material:
Steel, ams 6324

## **NSN 5365-00-910-5248**Externally Threaded Ring - Page 2 of 2



Material:
Steel comp 8740
Surface Treatment:
Cadmium
Surface Treatment:
Cadmium plated
Fsc Application Data:
Lower bearing, main landing gear, aircraft
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: T252-d