## NSN 5365-00-912-5295

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-912-5295 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 45.0 **Chamfer Length:** 0.025 inches **Overall Length:** 0.200 inches Diameter: 0.125 inches **Thread Size:** 1.ln.-32 **Bore Diameter:** 0.532 inches Depth: 0.100 inches

| Bore Shape:                                  |
|--|
| Straight                                     |
| Screw Thread Series Designator:              |
| Ns   |
| Drive Type:                                  |
| Drilled face                                 |
| Accommodation Type And Quantity:             |
| 4 holes                                      |
| Angle Between Accommodations In Deg:         |
| 90.0   |
| Radius From Geometric Axis To Accommodation: |
| 0.375 inches                                 |
| Beveled Thread:                              |
| Not included                                 |
| Bore Annular Internal Serration:             |
| Not included                                 |
| Setscrew Locking Notch:                      |
| Not included                                 |
| Bore Edge Process:                           |
| Chamfered                                    |
| Process End Location:                        |
| Both ends                                    |
|  |
|  |
|  |

## NSN 5365-00-912-5295

Externally Threaded Ring - Page 2 of 2



| ate |  |
|-----|--|
|     |  |
|     |  |

Steel, mil-s-6758, cond d4

Material:

Steel comp 4130

**Surface Treatment:** 

Cadmium

**Surface Treatment:** 

Cadmium plated

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T252-d