NSN 5365-00-913-6417

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-913-6417 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Width: Between 0.045 inches and 0.055 inches **Overall Length:** 0.234 inches **Thread Size:** 0.438-32 **Bore Diameter:** 0.234 inches Depth: Between 0.051 inches and 0.061 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Un **Drive Type:** Slotted face **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Special Features:** Bore counterbored 0.090 in. Deep; 0.3132 in. Diameter Material: Steel, astm a582, type 303 Material: Steel comp 303 **Surface Treatment: Passivate**

Surface Treatment:

Passivated, qq-p-35, type 2

NSN 5365-00-913-6417

Externally Threaded Ring - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d