## NSN 5365-00-914-0706

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-914-0706

Thread Class:
2a
Thread Direction:
Right-hand
Casehardening Indicator:
Not casehardened
Width:
0.060 inches
Overall Length:
Between 0.250 inches and 0.260 inches
Thread Size:
1/4 in28
Bore Diameter:
Between 0.123 inches and 0.128 inches
Depth:
Between 0.060 inches and 0.070 inches
Bore Shape:
Straight
Screw Thread Series Designator:
Unf
Drive Type:
Slotted face
Material Hardness Rating:
105.0 rockwell b
Thread Location:
Both ends
Accommodation Type And Quantity:
2 slots
Angle Between Accommodations In Deg:
180.0
Beveled Thread:
Included
Bore Annular Internal Serration:
Not included
Setscrew Locking Notch:
Not included
Material:
Steel, qq-s-763, class 303 or steel, qq-s-763, class 303se or steel, qq-s-763, class 304
Material:
Steel comp 303 or steel comp 303se or steel comp 304
Surface Treatment:
Passivate

## NSN 5365-00-914-0706

Externally Threaded Ring - Page 2 of 2



	Trea		

Passivated

**Fsc Application Data:** 

Fuel control, jet engine, aircraft

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T252-d