NSN 5365-00-936-2716

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-936-2716

| Thread Pitch Diameters: |
|---|
| +1.2360/+1.2390 inches |
| Thread Direction: |
| Right-hand |
| Casehardening Indicator: |
| Not casehardened |
| Chamfer Angle In Deg: |
| 45.0 |
| Chamfer Length: |
| Between 0.040 inches and 0.070 inches |
| Overall Length: |
| Between 0.235 inches and 0.245 inches |
| Diameter: |
| Between 0.095 inches and 0.115 inches |
| Thread Size: |
| 1.280-16 |
| Depth: |
| 0.220 inches |
| Screw Thread Series Designator: |
| Uns |
| Drive Type: |
| Drilled periphery |
| Material Hardness Rating: |
| Between 32.0 rockwell c and 38.0 rockwell c |
| Accommodation Type And Quantity: |
| 8 holes |
| Angle Between Accommodations In Deg: |
| 45.0 |
| Beveled Thread: |
| Not included |
| Bore Annular Internal Serration: |
| Not included |
| Setscrew Locking Notch: |
| Not included |
| Bore Edge Process: |
| Chamfered |
| Process End Location: |
| Both ends |
| Material: |
| Steel, ams6322 |
| Material: |
| Steel, ams6322 |
| Oleel, allisuuzz |

NSN 5365-00-936-2716

Externally Threaded Ring - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d