

View Online at <https://aerobasegroup.com/nsn/5365-00-950-2665>

**Thread Pitch Diameters:**

+3.4352/+3.4402 inches

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Chamfer Angle In Deg:**

45.0

**Chamfer Length:**

0.015 inches

**Width:**

0.046 inches

**Overall Length:**

0.400 inches

**Thread Size:**

3-15/32 in. -24

**Bore Diameter:**

2.843 inches

**Depth:**

0.078 inches

**Bore Shape:**

Straight

**Screw Thread Series Designator:**

Uns

**Drive Type:**

Slotted face

**Thread Location:**

Drive end

**Accommodation Type And Quantity:**

2 slots

**Angle Between Accommodations In Deg:**

180.0

**Beveled Thread:**

Not included

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Not included

**Bore Edge Process:**

Chamfered

**Process End Location:**

End opposite drive end

**Material:**

Steel, qq-s-763, class 303

**Material:**

Steel comp 303

**Surface Treatment:**

Passivate

**Surface Treatment:**

Passivated

**Fsc Application Data:**

Drive, ballistic, m10, fire control computing sights

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T252-d