

View Online at <https://aerobasegroup.com/nsn/5365-00-965-7414>

**Thread Pitch Diameters:**

+0.7269/+0.7297 inches

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Chamfer Angle In Deg:**

45.0 and 30.0

**Chamfer Length:**

Between 0.015 inches and 0.020 inches

**Width:**

0.062 inches

**Overall Length:**

0.159 inches

**Thread Size:**

3/4 in. -32

**Bore Diameter:**

0.500 inches

**Depth:**

0.050 inches

**Bore Shape:**

Straight

**Screw Thread Series Designator:**

Uns

**Drive Type:**

Slotted face

**Thread Location:**

Both ends

**Accommodation Type And Quantity:**

2 slots

**Angle Between Accommodations In Deg:**

180.0

**Beveled Thread:**

Included

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Not included

**Bore Edge Process:**

Chamfered

**Process End Location:**

Both ends

**Material:**

Steel, qq-s-763, class 416, cond h

**Material:**

Steel comp 416

**Surface Treatment:**

Passivate

**Surface Treatment:**

Passivated

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T252-d