## NSN 5365-00-965-7414

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-965-7414

Inread Pitch Diameters:
+0.7269/+0.7297 inches
Thread Direction:
Right-hand
Casehardening Indicator:
Not casehardened
Chamfer Angle In Deg:
45.0 and 30.0
Chamfer Length:
Between 0.015 inches and 0.020 inches
Width:
0.062 inches
Overall Length:
0.159 inches
Thread Size:
3/4 in32
Bore Diameter:
0.500 inches
Depth:
0.050 inches
Bore Shape:
Straight
Screw Thread Series Designator:
Uns
Drive Type:
Slotted face
Thread Location:
Both ends
Accommodation Type And Quantity:
2 slots
Angle Between Accommodations In Deg:
180.0
Beveled Thread:
Included
Bore Annular Internal Serration:
Not included
Setscrew Locking Notch:
Not included
Bore Edge Process:
Chamfered
Process End Location:
Both ends

## NSN 5365-00-965-7414

Externally Threaded Ring - Page 2 of 2



Material:
Steel, qq-s-763, class 416, cond h
Material:
Steel comp 416
Surface Treatment:
Passivate
Surface Treatment:
Passivated
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: T252-d