NSN 5365-00-999-5149

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-999-5149 **Thread Pitch Diameters:** +0.4827/+0.4856 inches **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 15.0 **Chamfer Length:** 0.016 inches **Overall Length:** 0.161 inches Diameter: 0.035 inches **Thread Size:** 1/2/0.500 in./-48 **Bore Diameter:** 0.327 inches Depth: 0.105 inches Bore Shape: Straight **Screw Thread Series Designator:** Uns **Drive Type:** Drilled face **Thread Location:** Both ends **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: **Radius From Geometric Axis To Accommodation:** 0.200 inches **Beveled Thread:** Included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:**

Included **Bore Edge Process:**Chamfered

NSN 5365-00-999-5149Externally Threaded Ring - Page 2 of 2



Process End Location:
Drive end
Material:
Steel, qq-s-763, class 316, cond a
Material:
Steel comp 316
Surface Treatment:
Passivate
Surface Treatment:
Passivated
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: T252-d