

View Online at <https://aerobasegroup.com/nsn/5365-01-006-9284>

Thread Class:

2a

Thread Direction:

Right-hand

Casehardening Indicator:

Not casehardened

Overall Length:

0.350 inches

Thread Size:

1.250-18

Bore Shape:

Straight

Screw Thread Series Designator:

Unef

Drive Type:

Any acceptable

Thread Location:

Both ends

Beveled Thread:

Included

Bore Annular Internal Serration:

Not included

Setscrew Locking Notch:

Included

Bore Edge Process:

Chamfered

Process End Location:

Both ends

Material:

Aluminum alloy qq-a-200/8 temper t6 or aluminum alloy qq-a-225/8 temper t6 or t651 or aluminum alloy qq-a-250/11 temper t6 or t651

Material:

Aluminum alloy qq-a-200/8 temper t6 or aluminum alloy qq-a-225/8 temper t6 or t651 or aluminum alloy qq-a-250/11 temper t6 or t651

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541 class 3 military specification single treatment response

Surface Treatment:

Chromate mil-c-5541 class 3

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d

Mil-std (military Standard):

Mil-c-5541 spec.