NSN 5365-01-007-9188

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-007-9188

Thread Pitch Diameters:
+3.2827/+3.2876 inches
Thread Direction:
Right-hand
Casehardening Indicator:
Not casehardened
Chamfer Angle In Deg:
45.0
Chamfer Length:
Between 0.015 inches and 0.050 inches
Width:
Between 0.255 inches and 0.261 inches
Overall Length:
0.600 inches
Thread Size:
3.330-16
Bore Diameter:
2.750 inches
Depth:
0.190 inches
Bore Shape:
Straight
Screw Thread Series Designator:
Screw Thread Series Designator: Uns
_
Uns
Uns Drive Type:
Uns Drive Type: Slotted face
Uns Drive Type: Slotted face Thread Location:
Uns Drive Type: Slotted face Thread Location: Both ends
Uns Drive Type: Slotted face Thread Location: Both ends Accommodation Type And Quantity:
Uns Drive Type: Slotted face Thread Location: Both ends Accommodation Type And Quantity: 3 slots
Uns Drive Type: Slotted face Thread Location: Both ends Accommodation Type And Quantity: 3 slots Angle Between Accommodations In Deg:
Uns Drive Type: Slotted face Thread Location: Both ends Accommodation Type And Quantity: 3 slots Angle Between Accommodations In Deg: 120.0
Uns Drive Type: Slotted face Thread Location: Both ends Accommodation Type And Quantity: 3 slots Angle Between Accommodations In Deg: 120.0 Beveled Thread:
Uns Drive Type: Slotted face Thread Location: Both ends Accommodation Type And Quantity: 3 slots Angle Between Accommodations In Deg: 120.0 Beveled Thread: Included
Uns Drive Type: Slotted face Thread Location: Both ends Accommodation Type And Quantity: 3 slots Angle Between Accommodations In Deg: 120.0 Beveled Thread: Included Bore Annular Internal Serration:
Uns Drive Type: Slotted face Thread Location: Both ends Accommodation Type And Quantity: 3 slots Angle Between Accommodations In Deg: 120.0 Beveled Thread: Included Bore Annular Internal Serration: Not included
Uns Drive Type: Slotted face Thread Location: Both ends Accommodation Type And Quantity: 3 slots Angle Between Accommodations In Deg: 120.0 Beveled Thread: Included Bore Annular Internal Serration: Not included Setscrew Locking Notch:
Uns Drive Type: Slotted face Thread Location: Both ends Accommodation Type And Quantity: 3 slots Angle Between Accommodations In Deg: 120.0 Beveled Thread: Included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included
Uns Drive Type: Slotted face Thread Location: Both ends Accommodation Type And Quantity: 3 slots Angle Between Accommodations In Deg: 120.0 Beveled Thread: Included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Bore Edge Process:

NSN 5365-01-007-9188

Externally Threaded Ring - Page 2 of 2



Material:	
Steel ams 6381	
Material:	
Steel ams 6381	
Surface Treatment:	
Cadmium plate mcair ps13101	type 2 cl 2 94641
Surface Treatment:	
Cadmium plate mcair ps13101	type 2 cl 2 94641
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

Fiig: T252-d