

NSN 5365-01-008-8012 Externally Threaded Ring - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5365-01-008-8012 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 45.0 **Chamfer Length:** Between 0.030 inches and 0.060 inches **Overall Length:** 2.000 inches Diameter: Between 3.8734 inches and 3.8739 inches **End Radius:** Between 1.9367 inches and 1.9369 inches **Thread Size:** 3.875-16 **Bore Diameter:** Between 3.5950 inches and 3.5955 inches Depth: Between 0.378 inches and 0.402 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Unj **Drive Type:** Drilled periphery **Accommodation Type And Quantity:**

4 holes

Angle Between Accommodations In Deg:

00 0

Radius From Geometric Axis To Accommodation:

Between 1.7975 inches and 1.7977 inches

Beveled Thread:

Not included

Bore Annular Internal Serration:

Not included

Setscrew Locking Notch:

Not included

Bore Edge Process:

Chamfered and rounded

NSN 5365-01-008-8012

Externally Threaded Ring - Page 2 of 2



Process End Location:

Drive end and end opposite drive end

Material:

Aluminum alloy, qq-a-200/3

Material:

Aluminum alloy 2024

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d