NSN 5365-01-023-2804

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-023-2804

Inread Pitch Diameters:
+1.2247/+1.2286 inches
Thread Direction:
Right-hand
Casehardening Indicator:
Not casehardened
Width:
0.062 inches
Overall Length:
0.125 inches
Thread Size:
1.250-32
Bore Diameter:
0.750 inches
Depth:
0.062 inches
Bore Shape:
Straight
Screw Thread Series Designator:
Uns
Drive Type:
Slotted face
Thread Location:
Both ends
Accommodation Type And Quantity:
2 slots
Angle Between Accommodations In Deg:
180.0
Beveled Thread:
Included
Bore Annular Internal Serration:
Not included
Setscrew Locking Notch:
Not included
Material:
Cres astm a582 comp 303
Material:
Cres astm a582 comp 303
Surface Treatment:
Passivate
Surface Treatment:
Passivated, mil-f-14072, finish e300

NSN 5365-01-023-2804

Externally Threaded Ring - Page 2 of 2



_				-		
C	h	Δ	Iŧ.		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d