## NSN 5365-01-029-8790

Plate Spacer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-029-8790

**Hole Diameter:** 

Between 0.215 inches and 0.223 inches

**Overall Length:** 

Between 1.990 inches and 2.010 inches

Overall Width:

Between 1.990 inches and 2.010 inches

**Aperture Diameter:** 

Between 0.990 inches and 1.010 inches

**Outside Corner Bevel Length Along Width:** 

Between 0.230 inches and 0.250 inches

**Outside Corner Bevel Length Along Length:** 

Between 0.230 inches and 0.250 inches

Center To Center Distance Between Bolt Holes Along Width:

1.414 inches

Center To Center Distance Between Bolt Holes Along Length:

1.414 inches

Outside Edge To Bolt Hole Center Distance Along Width:

Between 0.288 inches and 0.298 inches

Outside Edge To Bolt Hole Center Distance Along Length:

Between 0.288 inches and 0.298 inches

**Bolt Hole Quantity:** 

4

**Special Features:** 

Aperture counterbored one side 1.475 in. Min, 1.490 in. Maximum dia, 0.040 in. Min, 0.050 in. Maximum depth

Material:

Aluminum alloy 6061

**Material Specification:** 

Qq-a-250/11 federal specification single material response or qq-a-225/8 federal specification single material response

**Surface Treatment:** 

Anodize

**Surface Treatment Specification:** 

Mil-a-8625, type 2, cl 1 military specification single treatment response

**Style Designator:** 

Non-circular w/bolt holes

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A07000

## NSN 5365-01-029-8790

Plate Spacer - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.