NSN 5365-01-033-1324

Externally Threaded Ring - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5365-01-033-1324



Thread Class: 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Width: Between 0.085 inches and 0.095 inches **Overall Length:** Between 0.834 inches and 0.837 inches **Thread Size:** 1.000-16 **Bore Diameter:** Between 0.365 inches and 0.385 inches Depth: 0.160 inches Bore Shape: Straight **Screw Thread Series Designator:** Un **Drive Type:** Slotted face **Material Hardness Rating:** Between 38.0 rockwell c and 45.0 rockwell c **Thread Location:** Both ends **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: 60.0 **Beveled Thread:** Included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Special Features:** Counterbore 0.500 in. Diameter by 0.470 in. Deep and slot in drive end @0.186 in. W by 0.190 in. Deep Material: Steel, ams 5610 Material: Steel comp 416se

NSN 5365-01-033-1324

Externally Threaded Ring - Page 2 of 2



	Trea	

Passivate astm a380

Surface Treatment:

Passivate astm a380

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d