NSN 5365-01-037-3992

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-037-3992

Thread Pitch Diameters:
+0.8810/+0.8840 inches
Thread Direction:
Right-hand
Casehardening Indicator:
Not casehardened
Width:
0.062 inches
Overall Length:
0.110 inches
Thread Size:
0.906-32
Bore Diameter:
0.703 inches
Depth:
0.062 inches
Bore Shape:
Straight
Screw Thread Series Designator:
Nonstandard
Drive Type:
Slotted face
Material Hardness Rating:
Between 39.0 rockwell c and 47.0 rockwell c
Accommodation Type And Quantity:
2 slots
Angle Between Accommodations In Deg:
180.0
Beveled Thread:
Not included
Bore Annular Internal Serration:
Not included
Setscrew Locking Notch:
Not included
Material:
Steel, ams 5643, 17-4ph
Material:
Steel comp 630
Surface Treatment:
Passivate
Surface Treatment:

Passivated, qq-p-35

NSN 5365-01-037-3992

Externally Threaded Ring - Page 2 of 2



_				-		
C	h	Δ	Iŧ.		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d