NSN 5365-01-040-4429

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-040-4429 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Width: Between 0.380 inches and 0.400 inches **Overall Length:** 1.000 inches **Thread Size:** 4.250-12 **Bore Diameter:** 3.690 inches Depth: Between 0.360 inches and 0.400 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Un **Drive Type:** Slotted face **Material Hardness Rating:** Between 33.0 rockwell c and 38.0 rockwell c **Accommodation Type And Quantity:** 6 slots Angle Between Accommodations In Deg: 60.0 **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included Material: Phosphate coated, manganese base

Steel, astm a400 Material: Steel **Surface Treatment:** Shelf Life: N/a

NSN 5365-01-040-4429

Externally Threaded Ring - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|-----|-----|------|
| In | 18 | <i>(</i>)+ | МЛО | 201 | ure: |
| | | | | | |

--

Demilitarization:

No

Fiig:

T252-d