## NSN 5365-01-046-2461

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-046-2461

| Thread Pitch Diameters:  |
|--|
| +3.3654/+3.3708 inches   |
| Thread Direction:  |
| Right-hand   |
| Casehardening Indicator:   |
| Not casehardened   |
| Width:   |
| 0.188 inches   |
| Overall Length:  |
| 0.312 inches   |
| Thread Size:   |
| 3.406-16   |
| Bore Diameter:   |
| 3.078 inches   |
| Depth:   |
| 0.094 inches   |
| Bore Shape:  |
| Straight   |
| Screw Thread Series Designator:  |
| Special  |
| Drive Type:  |
| Slotted face   |
| Accommodation Type And Quantity:   |
| 2 slots  |
| Angle Between Accommodations In Deg:   |
| 180.0  |
| Beveled Thread:  |
| Not included   |
| Bore Annular Internal Serration:   |
| Not included   |
| Setscrew Locking Notch:  |
| Not included   |
| Bore Edge Process:   |
| Any acceptable   |
| Material:  |
| Copper alloy qq-c-390 or copper alloy astm b62 alloy 4a or copper alloy astm b145 alloy 4a |
| Material:  |
| Copper alloy qq-c-390 or copper alloy astm b62 alloy 4a or copper alloy astm b145 alloy 4a |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |

--

## NSN 5365-01-046-2461

Externally Threaded Ring - Page 2 of 2



Demilitarization:

No

Fiig:

T252-d