

View Online at <https://aerobasegroup.com/nsn/5365-01-046-4256>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Chamfer Angle In Deg:**

45.0

**Chamfer Length:**

0.015 inches

**Overall Length:**

0.188 inches

**Diameter:**

Between 0.156 inches and 0.161 inches

**Thread Size:**

1.437-18

**Bore Diameter:**

Between 0.900 inches and 0.910 inches

**Depth:**

0.188 inches

**Bore Shape:**

Straight

**Screw Thread Series Designator:**

Unef

**Drive Type:**

Drilled face

**Thread Location:**

Both ends

**Accommodation Type And Quantity:**

2 holes

**Angle Between Accommodations In Deg:**

180.0

**Radius From Geometric Axis To Accommodation:**

0.594 inches

**Beveled Thread:**

Included

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Not included

**Bore Edge Process:**

Chamfered

**Process End Location:**

Both ends

**Material:**

Cres astm a582 type 416 cond a or cres astm a582 type 416 cond t

**Material:**

Cres astm a582 type 416 cond a or cres astm a582 type 416 cond t

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 type 4 federal specification single treatment response

**Surface Treatment:**

Passivated qq-p-35 type 4

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T252-d