NSN 5365-01-046-4256

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-046-4256 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 45.0 **Chamfer Length:** 0.015 inches **Overall Length:** 0.188 inches Diameter: Between 0.156 inches and 0.161 inches **Thread Size:** 1.437-18 **Bore Diameter:** Between 0.900 inches and 0.910 inches Depth: 0.188 inches Bore Shape: Straight **Screw Thread Series Designator:** Unef **Drive Type:** Drilled face **Thread Location:** Both ends **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: **Radius From Geometric Axis To Accommodation:** 0.594 inches **Beveled Thread:** Included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:**

Not included

Bore Edge Process:

Chamfered

NSN 5365-01-046-4256

Externally Threaded Ring - Page 2 of 2



Process End Location:
Both ends
Material:
Cres astm a582 type 416 cond a or cres astm a582 type 416 cond t
Material:
Cres astm a582 type 416 cond a or cres astm a582 type 416 cond t
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 type 4 federal specification single treatment response
Surface Treatment:
Passivated qq-p-35 type 4
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

T252-d