NSN 5365-01-046-5869



Externally Threaded Ring - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5365-01-046-5869 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Overall Length:** 0.688 inches Diameter: 0.062 inches **Thread Size:** 1.188-28 **Bore Diameter:** 0.688 inches Depth: 0.078 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Un **Drive Type:** Drilled periphery **Thread Location:** End opposite drive end **Accommodation Type And Quantity:** 6 holes Angle Between Accommodations In Deg: **Radius From Geometric Axis To Accommodation:** 0.562 inches **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Bore Edge Process:** Any acceptable **Special Features:** Drive end counterbored 0.969 in. Dia

Material:

Cres astm a582 type 303 cond a or cres astm a582 type 303se cond a

NSN 5365-01-046-5869

Externally Threaded Ring - Page 2 of 2



Material:
Cres astm a582 type 303 cond a or cres astm a582 type 303se cond a
Surface Treatment:
Passivate
Surface Treatment:
Passivated, qq-p-35
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

T252-d