NSN 5365-01-046-5870

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-046-5870 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Overall Length:** 0.082 inches Diameter: 0.078 inches **Thread Size:** 0.688-40 **Bore Diameter:** 0.312 inches Depth: 0.050 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Uns **Drive Type:** Drilled face **Accommodation Type And Quantity:** 2 holes Angle Between Accommodations In Deg: 180.0 **Radius From Geometric Axis To Accommodation:** 0.242 inches **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Bore Edge Process:** Any acceptable **Special Features:** Counterbored 0.562 in. Min 0.594 in. Maximum dia Material: Cres astm a582 type 303 cond a

Cres astm a582 type 303 cond a

Material:
Cres astm a582 type 303 cond a

NSN 5365-01-046-5870

Externally Threaded Ring - Page 2 of 2



_	•		_	-		
ن	ırfa	\sim	I ro	-atn	nor	٠.

Passivate

Surface Treatment:

Passivated, qq-p-35

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d