## NSN 5365-01-048-3048

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-01-048-3048 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Overall Length:** 0.300 inches Diameter: 0.125 inches **Thread Size:** 6.219-32 **Bore Diameter:** Between 5.550 inches and 5.570 inches Depth: 0.156 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Uns **Drive Type:** Drilled face **Accommodation Type And Quantity:** 4 holes Angle Between Accommodations In Deg: 180.0 **Radius From Geometric Axis To Accommodation:** 2.930 inches **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Bore Edge Process:** Any acceptable **Special Features:** Fifteen 0.164-32 unc-3b thread holes equally spaced on face Material: Steel, qq-s-766, class 304, cond a or cres qq-s-766 cl 302 cond a or cres qq-s-766 cl 305 cond a

Material:

Steel comp 304 or cres qq-s-766 cl 302 cond a or cres qq-s-766 cl 305 cond a

## NSN 5365-01-048-3048

Externally Threaded Ring - Page 2 of 2



Material Specification:
Qq-s-766, class 304, cond a federal specification 1st material response
Surface Treatment:
Passivate
Surface Treatment:
Passivated, qq-p-35
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

T252-d